

§ 1918.34

§ 1918.34 Other decks.

(a) Cargo shall not be worked on decks that were not designed to support the load being worked.

(b) Grated decks shall be properly placed, supported, maintained and designed to support employees.

§ 1918.35 Open hatches.

Open weather deck hatches around which employees must work that are not protected to a height of 24 inches (.61 m) by coamings shall be guarded by taut lines or barricades at a height of 36 to 42 inches (.91 to 1.07 m) above the deck, except on the side on which cargo is being worked. Any portable stanchions or uprights used shall be supported or secured to prevent accidental dislodgement.

§ 1918.36 Weather deck rails.

Removable weather deck rails shall be kept in place except when cargo operations require them to be removed, in which case they shall be replaced as soon as such cargo operations are completed.

§ 1918.37 Barges.

(a) Walking shall be prohibited along the sides of covered lighters or barges with coamings or cargo more than five feet (1.52 m) high unless a three-foot (.91 m) clear walkway or a grab rail or taut handline is provided.

(b) Walking or working shall be prohibited on the decks of barges to be loaded unless the walking or working surfaces have been determined by visual inspection to be structurally sound and maintained properly. If, while discharging a barge, an unsound deck surface is discovered, work shall be discontinued and shall not be resumed until means have been taken to ensure a safe work surface.

[62 FR 40202, July 25, 1997, as amended at 65 FR 40944, June 30, 2000]

Subpart E—Opening and Closing Hatches

§ 1918.41 Coaming clearances.

(a) *Weather decks.* If a deck load (such as lumber or other smooth sided deck cargo) more than five feet (1.52 m) high is stowed within three feet (.91 m) of

29 CFR Ch. XVII (7–1–10 Edition)

the hatch coaming and employees handling hatch beams and hatch covers are not protected by a coaming at least 24-inch (.61 m) high, a taut handline shall be provided along the side of the deckload. The requirements of §1918.35 are not intended to apply in this situation.

(b) *Intermediate decks.* (1) There shall be a three-foot (.91 m) working space between the stowed cargo and the coaming at both sides and at one end of the hatches with athwartship hatch beams, and at both ends of those hatches with fore and aft hatch beams, before intermediate deck hatch covers and hatch beams are removed or replaced. Exception: The three-foot (.91 m) clearance is not required on the covered portion of a partially open hatch, nor is it required when lower decks have been filled to hatch beam height with cargo of such a nature as to provide a safe surface upon which employees may work.

(2) For purposes of paragraph (b)(1) of this section, fitted gratings that are in good condition shall be considered a part of the decking when properly placed within the three-foot (.91 m) area.

(c) Grab rails or taut handlines shall be provided for the protection of employees handling hatch beams and hatch covers, when bulkheads, lockers, reefer compartments or large spare parts are within three feet (.91 m) of the coaming.

(d) The clearances in this section do not apply to hatches opened or closed solely by hydraulic or other mechanical means; except that, in all cases in which the three-foot (.91 m) clearance does not exist, cargo that is stowed within three feet (.91 m) of the edge of the hatch shall be adequately secured to prevent cargo from falling into the hold.

[62 FR 40202, July 25, 1997, as amended at 65 FR 40944, June 30, 2000]

§ 1918.42 Hatch beam and pontoon bridges.

(a) Hatch beam and pontoon bridges shall be:

(1) Long enough to reach the holes, rings, or other lifting attachments on the hatch beams and pontoons easily;